Remover Pro

Concentrated, wax-removing detergent for the removal of residual wax, oil and grease from resin, resilient materials, marble, ceramic floors.



Remover Pro is specifically intended for the preparation of Cementoresina and Microresina Floor continuous floorings before applying Care Pro. Suitable for degreasing and thorough cleaning of ceramic, porcelain tiles and marble floors before overlaying with inorganic mineral adhesives of the H40 range.

1. Concentrate, with a high level of wax-removing and degreasing power
2. Suitable to remove old layers of Refresher and Care Pro
3. Effectively cleans floors before overlaying with H40 Gel and H40 Advanced

kerakoll

Areas of application

→ Use
Professional wax-removing treatment to clean and remove Refresher, Care Pro or waxes and acrylic protective layers dispersed in water from:
- Cementoresina continuous floors
- Microresina Floor continuous floors
- Legno+Color floors
- pre-finished hardwood floors
- floors in PVC, rubber, linoleum, etc

For thorough cleaning of ceramic, porcelain tiles and natural stone floors before overlaying with inorganic mineral adhesives of the H40 range.
Internal floors in domestic, commercial and industrial environments.

Do not use pure (undiluted) for the cleaning of floors on which new flooring must not be laid.
Do not use pure (undiluted) for the cleaning of wooden floors. For removing layers of waxes and solvents.

Instructions for use

→ Preparation
The product is ready-to-use.
To prepare floors before applying Care Pro: dilute 1 part of Remover with 5 to 10 parts of warm water. Work on small areas at a time, of ≈ 3 m².
For thorough cleaning and degreasing of ceramic, porcelain tiles and natural stone floors before overlaying with inorganic mineral adhesives of the H40 range: dilute 1 part of Remover Pro with 1 part of warm water.

→ Application
Apply the solution on the floor and leave it to work for ≈ 5 minutes. Rub with a cloth and large brush or wipe with a floor cleaning machine equipped with a stiff brush and collect the dirt removed. Repeatedly rinse with clean water to remove all the residues of dirt and waxes.
Check that the layers of dirt and wax have been completely removed, then dry the surface. It is suggested to protect furniture and skirting boards adjacent to the working area. Make sure that the floor is completely dry before the application of the next passage.

Special notes

→ In treating stubborn stains, it is recommended that a buffer with white fabric cleaning disc such as Pad be used to wash the floor; it is suggested that a suitable vacuum cleaner for liquids be used to remove any excess water left on the floor after rinsing.
→ If thick or very old layers have to be removed, then a greater concentration and a longer waiting time are recommended.
→ Do not leave Remover Pro solution to dry on the floor: if necessary wet it again with a little lukewarm water to avoid stains forming.
→ Check colour resistance before using it to clean linoleum floors: if necessary apply a more diluted solution and leave it to work more briefly.
→ Composition (CEE 89/542 Recommendations) non-ionic surfactants: 10 – 15 %, non-chlorinated organic solvents: 15 – 20 %; phosphates: less than 2 % (P < 0.5).
→ Biodegradability: above 90 % (Art. 7 Law 26.04.1983 Nr. 136).

Technical Data compliant with Kerakoll Quality Standard	
Appearance	Transparent liquid
Pack	can 2.5 l
Shelf life	≈ 12 months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C
Drying	≈ 1 hr
Dilution	between 1:1 and 1:10 with pure water
Coverage:	
- diluted product 1:5 – 1:10	≈ 20 – 30 ml/m²
- diluted product 1:1	≈ 200 – 300 ml/m²

Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

Warning

→ Product for professional use
→ abide by any standards and national regulations
→ dispose of as indicated in applicable legislation
→ protect any surfaces and objects in the application area from accidental contact with the product
→ read the product safety data sheet before use
→ for any other issues, contact the Kerakoll Worldwide Global Service - info@kerakoll.ae

This information was last updated in September 2026; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.

Kerakoll Gulf Trading LLC
Concord Tower, Al Sofouh 2
Dubai UAE

+971 (0)4 298 5715
info@kerakoll.ae

www.kerakoll.com