CLEANER L

Cleaning solution for pre-finished parquet





WHERE TO USE

Cleaning solution for pre-finished parquet and timber flooring.

Some application examples

Cleaner L is used for cleaning pre-finished painted parquet which has been stained with traces of two-component or single component, polyurethane adhesives.
It is also capable of removing adhesive which has partially set up to 4 hours after application at +23°C and 50% R.H.

TECHNICAL CHARACTERISTICS

Cleaner L is a mixture of low-volatility chemical substances with high solvent power.

RECOMMENDATIONS

Use the cleaning solution before the adhesive has completely set, within 4 hours.

APPLICATION PROCEDURE

Pour the amount of solution required onto a clean, cotton rag and gently rub on the newly-laid floor covering. Wait the desired amount of time before wiping off with a dry cloth.
Removal of residual adhesive from pre-finished, varnished parquet must be carried out immediately, and in all cases within a maximum of 4 hours. Any remaining stains may be removed up to the day after laying using **Cleaner L** and sawdust.
A light, oily film will form on the surface after cleaning, which may then be removed using any normal cleaning product.

CONSUMPTION

Varies according to the amount of contamination to be removed: 5-20 g/m^2.

PACKAGING

1 l canisters (0.85 kg).
Packs of 12 canisters.

STORAGE

24 months in its original, sealed container stored under normal conditions.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Cleaner L is not considered as dangerous according to the European regulation regarding the classification of mixtures. It is however recommended to use gloves, eye protection and to take the usual precaution when handling chemical products.
For further and complete information about a safety use of our product please refer to our latest version of the Material Safety Data Sheet.
PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY	
Consistency:	liquid
Colour:	transparent
Density:	0.95 g/cm³
Viscosity (Ø 4 Ford viscosity cup):	14 seconds
Storage:	24 months
Hazard classification according to EC 1999/45:	none. Before using refer to the “Safety instructions for preparation and application” paragraph and the information on the packaging and Safety Data Sheet
Customs class:	3814 00 90





WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of the product.
Please refer to the current version of the Technical Data Sheet, available from our web site www.mapei.com

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution