ULTRACARE FUGA FRESCA

Polymeric paint to refresh the colour of the cementitious grout joints between tiles





BENEFITS AND FEATURES

- Quick and easy to apply; shake/stir well before use
- Excellent covering power
- Protects joints and makes routine cleaning easier
- Available in 48 colours from the MAPEI coloured grouts range
- Residual Greenhouse Gas emissions fully offset

CO_2e FULLY OFFSET PRODUCTS

Residual Greenhouse Gas emissions measured throughout the life cycle of this product using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset for the year 2026 through the acquisition of carbon credits in support of forestry protection projects. For more details on emission calculations and offsetting projects, visit mapei.com.

WHERE TO USE

UltraCare Fuga Fresca is a ready-to-use paint that can easily and quickly renew or change the colour of cementitious grout lines in indoor floors and wall coverings.

Some application examples

UltraCare Fuga Fresca is used to eliminate colour inconsistencies in grout lines caused, for example, by improper application of the grouting mortar, or to eliminate unsightly stains resulting from use.

TECHNICAL CHARACTERISTICS

UltraCare Fuga Fresca is a water-based, polymeric, acrylic resin-based paint that, thanks to its special characteristics and excellent covering power, allows uniformly coloured joints with reduced water absorption and is therefore easier to clean.

RECOMMENDATIONS

- Do not use outdoors except in specific conditions. Contact Mapei Technical Services for further information.
- Do not use on surfaces subject to continuous immersion (swimming pools, basins, etc.).
- If the product is used on terracotta floors or on stone material with a porous, absorbent surface, it must only be applied on the joints to avoid staining the tiles.

- Apply the product on fully cured cementitious grout lines (time varies according to the specific type of grouting mortar).
- Do not use on epoxy grouts or on expansion joints sealed with silicone- or polyurethane-based products.
- Do not use **UltraCare Fuga Fresca** to consolidate grout lines that are loose or have poor mechanical strength due to improper hydration.
- If there is a noticeable difference between the old and new colour, multiple applications may be required.

APPLICATION PROCEDURE

Sponge applicator bottle

Shake the bottle thoroughly before use.

Unscrew the cap and apply the product by pressing the sponge applicator lightly on the surface of the joints, which must be clean and free from loose parts, mould, and limescale deposits.

Wait a few minutes until the product applied to the joints is dry (according to actual environmental conditions).

Remove any traces of the product from the edges of the tiles using the hard cellulose sponge **Mapei CELLULOSE Cleaning Grout Sponge**, dampened with water.

After use, thoroughly clean the sponge applicator.

Bucket

The product is ready to use.
Stir the product in the bucket thoroughly before use.

Using a brush of suitable size, spread the product on the surface of the joints, which must be clean and free from loose parts, mould, and limescale deposits.

Wait a few minutes until the product applied on the joints is dry.

Remove any traces of the product from the edges of the tiles using the hard cellulose sponge **Mapei CELLULOSE Cleaning Grout Sponge**, dampened with water.

CONSUMPTION

The consumption of **UltraCare Fuga Fresca** varies depending on the size of the tiles and grout lines.

PACKAGING

1 kg bucket, available in colours 100, 103, 110, 111, 112, 113, 114, 120, 130, and 132.
160 g sponge applicator bottle, available in all 48 colours of the MAPEI range.

COLOURS

Available in 48 colours from the MAPEI range.

Mapesil AC		
100	WHITE	
103	MOON WHITE	
110	MANHATTAN	

111	SILVER GREY	
112	MEDIUM GREY	
113	CEMENT GREY	
114	ANTHRACITE	
119	LONDON GREY	
120	BLACK	
123	ANCIENT WHITE	
127	ARCTIC GREY	
130	JASMINE	
132	BEIGE 2000	
133	SAND	
134	SILK	
135	GOLDEN DUST	
136	MUD	
137	CARIBBEAN	
138	ALMOND	
141	CARAMEL	
142	BROWN	
144	CHOCOLATE	
152	LIQUORICE	
187	LINEN	
188	BISCUIT	
601	OPTICAL WHITE	
602	INDUSTRIAL	
603	SKY	
604	BLUEBERRY	
605	ICEBERG	

606	DOLPHIN	
607	LEAD	
608	COTTON	
609	ROCK	
610	DUST	
611	LAGOON	
612	SHIST	
613	RICE	
614	LIGHT ASH	
615	ECRU	
616	WALNUT	
617	SOFT PEACH	
618	BRICK	
619	CLAY	
620	COFFEE	
621	HEMP	
622	DESERT	
623	CINNAMON	

Note: Due to the printing process involved, the colours shown are merely indicative

STORAGE

2 years in the original, closed packages and stored under normal conditions.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the SDS available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY	
Consistency:	thick liquid
Colour:	available in 48 colours.
Density:	1.37 g/cm³
pH:	9
Dry solids content:	62%
Brookfield viscosity:	8 Pa·s (# 6 - rpm 10)
Coverage power (contrast ratio):	96.93
Dirt pick-up (UNI 10792):	ΔE* 0,27
Resistance to abrasion (DIN 53778):	> 10,000 cycles
Weather-ometer resistance (ASTM G155) Cycle 1:	ΔE* 0,04
Application temperature:	from +5°C to +35°C
Set to foot traffic:	2 hours
Waiting time before putting the treated surface in contact with water:	24 hours

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

Mapei S.p.A.

Via Cafiero, 22, 20158, Milano

+39-02-376731 www.mapei.com mapei@mapei.it

11009-9-2026 en (IT)

Any reproduction of texts, photos, and illustrations published here is prohibited and subject to prosecution