
ULTRACARE INTENSIFIER S

Solvent-based color-enhancing sealer with high penetration capacity and protective and enhancing effect





BENEFITS AND FEATURES

- Quick and simple application
- UV resistant
- Enhances the colour of natural stone (including stone with a polished finish)
- Suitable for terracotta, terrazzo, marble-chip tiles, cementine tiles and engineered stone
- Ready to use
- Suitable for application on walls and floors, both in interior and exterior

WHERE TO USE

UltraCare Intensifier S is an innovative, solvent-based formulation used to enhance and preserve the colour of low-absorbing natural stone (with a polished surface) terrazzo, marble-chip tiles, cementine tiles and engineered stone in both internal and external surroundings.

TECHNICAL CHARACTERISTICS

When applied on the surface of the material, it enhances its colour and gives it a matt look finish. Its particular solvent-based formulation helps it absorb into the material, especially those which are particularly compact or have a polished finish. Suitable for application on internal and external floors and walls. Ideal for window ledges, doorsteps, decorative features and worktops.

UltraCare Intensifier S provides surfaces with a long-lasting and highly effective water and oil-resistant finish, protects them from staining and reduces their level of dirt pick-up.

It is resistant to traffic, UV stable, does not form a film on the surface and has very little effect on the breathability or anti-slip properties of the material. Surfaces can be treated with just one product.

RECOMMENDATIONS

- Always carry out a preliminary test on a sample area of the surface to verify its effect.
- Only apply the product on surfaces resistant to solvents and always wear suitable protective clothing.

- If the sole requirement is to provide surfaces with a water and oil-repellent finish and to protect them against staining, it is recommended to use **UltraCare Stain Protector W**, **Ultracare Stain Protector W Plus** or **UltraCare Stain Protector S** (please refer to respective Technical Data Sheets).
- Once **UltraCare Intensifier S** has been applied, surfaces cannot be returned to their original condition. Always perform a preliminary test on a small, unexposed area of the surface, or on a sample of the material to be treated, to verify the effect on the finish before applying the product to the entire surface.
- The treatment may be repeated after a certain period of time to maintain its effect, especially on external surfaces, and according to the type of material, its exposure to atmospheric agents and the levels of traffic and wear it has to withstand.
- Do not apply the product on exposed surfaces if rain is forecast within the next few hours after application.
- If the product is used in an interior space, ensure the room is well ventilated during application and drying.

APPLICATION PROCEDURE

The product is supplied ready to use. Shake well before application.

Make sure the substrate is completely dry and clean and apply **UltraCare Intensifier S** with a brush, roller or fleece applicator. Spread the product evenly over the surface to be treated with a cloth to help it penetrate the material and remove any excess wet product before it dries (5-10 minutes in normal conditions). Surfaces may be opened to foot traffic 8 hours after application (when applied at +23°C with 50% R.H.; actual time depends on environmental conditions and the material's absorbency rate).

To further enhance the material's colour, and depending on its absorbency, additional coats of the product may be applied, waiting one hour between applications and repeating the operations described above.

CONSUMPTION

Up to 30 m^2 surface with 1 litre of **UltraCare Intensifier S** (one coat). Yield is strongly influenced by the absorbency and surface finish of the substrate to be treated.

PACKAGING

UltraCare Intensifier S is supplied in 1 litre jerrycans.

STORAGE

3 years in its original unopened packaging.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found in the latest version of the Safety Data Sheet, available on our website at www.mapei.ae.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY	
Consistency:	homogeneous liquid
Colour:	transparent
Density at +20°C:	0.82 g/cm^3

APPLICATION DATA	
Dilution ratio:	ready to use
Surface drying:	2-3 hours
Application temperature range:	+5°C to +35°C

IMPORTANT NOTES

While we try to ensure that any advice, recommendations, or information in our literature is accurate and correct, we have no control over the circumstances in which our product is used. It is, therefore, important that installers satisfy themselves that the product and conditions are suitable for the envisaged application. No warranty can be given, nor can responsibility be accepted, other than the product we supply will meet our written specifications. The installer should ensure that our latest product data and safety information sheets have been consulted before use.

Please refer to the current version of the Technical Data Sheet, available on our website www.mapei.ae.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into other project-related documents. The resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation. The most up-to-date TDS can be downloaded from our website, www.mapei.ae.

ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDE THE RESPONSIBILITY OF MAPEI.

All relevant references for the product are available upon request and from www.mapei.com.

Mapei Construction Chemicals L.L.C

Dubai Investment Park 2, P.O. Box: 73869, Dubai, United Arab Emirates

+971 4 815 6666 www.mapei.ae info@mapei.ae

11011-12-2025 (UAE)

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution