
CERFIX PROANGLE AX / METAL LINE AF – M DESIGN

External corner profiles
Listellos and decorative profiles




DESCRIPTION

M-Design is a range of finishing and transition profiles designed to give ceramic coverings a minimalist look with sharp edges and clean lines.
Cerfix Proangle AX is a profile in anodised or colour-coated aluminium, which finishes the vertical edge of the coverings, accentuating the discontinuity between the wall in an elegant way.
Metal Line AF is a decorative listello in anodised or colour-coated aluminium characterized by modern lines that, thanks to its special shape, creates an elegant shadow between floor covering and wall covering.
Anodised models are not recommended for outdoor use.



AX/2/



AF/1/

FEATURES AND BENEFITS

- Modern and minimalist design
- It protects the corners of ceramic coverings
- It prevents awkward 45° corner cutting of tiles
- Available heights from 6 to 12,5 mm

MATERIALS

Anodised aluminium
Colour - coated aluminium

For further information, please refer to the section “MATERIALS AND CHARACTERISTICS” at the end of the current Price List Catalogue.

INSTALLATION

Installation with adhesive
Use appropriate personal protective equipment (PPE), such as cut-resistant gloves, when handling the profile.
Remove the profile from its packaging.
Check that the thickness of the wall or floor covering to be installed does not exceed the height of the selected profile.
Where present, remove the protective and/or heat-shrink film used to protect the product finish.
Measure the length of the perimeter to be protected and pre-cut the profiles to size.
Apply the selected adhesive to the installation surface using a notched trowel and place the profile, aligning it flush with the already installed covering.
Install the remaining covering, ensuring it is flush with the profile and spaced at the appropriate distance to maintain the grout joint (usually between 1 and 2 millimetres).
Fill the joint between the covering and the profile with a suitable sealant.
Carefully clean the grout or any other installation residues using a soft sponge and water within 10 minutes of application.

CARE AND MAINTENANCE


The care and maintenance of the materials used for the manufacture of these profiles are closely related to the type of alloy and/or finish employed.
The following guidelines describe the operations required to restore the profile, as much as possible, to its original appearance.
These instructions are intended to provide general guidance on the timing and methods for cleaning; however, they must be assessed on a case-by-case basis.
It should be noted that specific responsibilities apply at every stage of the product's life cycle, starting from installation.

Aluminium
Aluminium does not require specific maintenance and can be easily cleaned using colourless alcohol diluted with water or neutral detergents diluted with water (e.g. products from the MAPEI ULTRACARE range). Do not use acidic or alkaline detergents.
Rinsing must be carried out using water only, with non-abrasive sponges and/or cloths to avoid scratching and/or damaging the finish.
No maintenance with polishing products or similar substances is required.
Cement, adhesive and grouting materials must be promptly and carefully removed from the visible surface of the profile.

FIRE PREVENTION MEASURES

In the event of fire, use chemical fire extinguishers, dry sand or solid extinguishing agents.

EXTERNAL CORNER PROFILES - LISTELLOS AND DECORATIVE PROFILES




AX/2/

PROANGLE AX- M DESIGN

length = 270 cm - pack 10 pcs			H		
ART.	**finishing**		**6**	**10**	**12,5**
ALUMINIUM					
AX/2/	silver anodised		13208	13209	13210
	titanium anodised		13211	13213	13212
	colour-coated polished white RAL 9010		13215	13216	13214

individually packed



AF/1/

METAL LINE AF - M DESIGN

length = 270 cm - pack 10 pcs			H		
ART.	**finishing**		**6**	**10**	**12,5**
ALUMINIUM					
AF/1/	silver anodised		13198	13199	13200
	titanium anodised		13201	13203	13202
	colour-coated polished white RAL 9010		13196	13197	13204

individually packed

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website profilpas.com

PRODUCT FOR PROFESSIONAL USE

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the PROFILPAS product installation.

The most up-to-date TDS can be downloaded from our website profilpas.com

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF PROFILPAS.

PRESCRIPTION

Supply and installation of a (...) profile (type CERFIX PROANGLE AX by Profilpas S.p.A.) with an "X" section, designed to act as an edge protection profile serving both as a finishing and protective solution for the external corners of ceramic tile coverings, avoiding the unattractive and fragile 45° bevel cut of tile edges.
The profile shall have a height of (...) mm and a length of 270 cm. Thanks to its dimensions, the profile may be installed without joints in a single continuous length, embedding the perforated lateral anchoring flange into the suitable adhesive selected for the installation of the ceramic flooring (e.g. products by Mapei S.p.A.).
During installation, the joint formed between the tile and the profile must be filled with a suitable sealant (e.g. products by Mapei S.p.A.). Any residues of adhesive, grout or sealant present on the profile must be removed immediately using non-abrasive tools. Upon completion of installation, any residual cementitious or epoxy materials may be removed using a suitable cleaning product (e.g. products from the MAPEI ULTRACARE range).

Profilpas S.p.A.

Via Albert Einstein, 38, 35010 Cadoneghe (Padova)

+39 049 8878411 www.profilpas.com info@profilpas.com

13322-13323-09-2026-en

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution.