CERFIX PROANGLE Q

External corners profiles



DESCRIPTION


Cerfix Proangle Q is a range of profiles particularly suitable for finishing and protecting the external corners of ceramic tile coverings. Its square shape clearly defines the edge, avoiding the unattractive and fragile 45° tile mitre cut.
The stainless steel and brass versions are also particularly suitable for finishing and protecting floors and stair edges in a wide variety of materials such as ceramic, stone, or other materials. They can also be used as finishing profiles for worktops and platforms.

Cerfix Proangle Q aluminium, available in a wide variety of decorative effects and finishes, is also used as a decorative listel or in combination with profiles from the Cerfix Prolist range, which are available in the same finishes. This results in refined and visually pleasing combinations or contrasts with a wide variety of coverings.


Cerfix Proangle Q stainless steel, available in polished or brushed finishes, is particularly resistant to chemical agents, atmospheric conditions, and mechanical stress. The version made of AISI 316 – DIN 1.4401 stainless steel offers improved corrosion resistance and is therefore recommended for applications in areas subject to higher chemical exposure.

Cerfix Proangle Q polished brass is a profile with a classic finish that can be combined with other furnishing elements such as handles, taps, and/or other accessories made of the same material and finish. The chromium-plated brass version stands out for the high brilliance of its surface.


Anodised and bright aluminium models are not recommended for outdoor use.
Chromium-plated brass models are not recommended for floor applications subject to heavy pedestrian traffic.
Special accessories are available for the creation of external/internal corners and end caps, ensuring uniformity and linear continuity of the finish.




ALUMINIUM / BRASS
H 4,5 MM



ALUMINIUM / BRASS
H 6 / 12,5 MM



STAINLESS STEEL
H 6 / 15 MM



CO-EXTRUDED PVC
H 6 / 12,5 MM

FEATURES AND BENEFITS

- Profile with modern and minimalist design
- It protects the corners of ceramic coverings
- It prevents awkward 45° corner cutting of tiles
- Available in aluminium, steel, brass and PVC
- Available heights from 4.5 to 15 mm
- The twenty Trend Colour finishes perfectly match the trendiest colours in the world of interior design and ceramic tiles
- X Design finishes available: 5 modern colours in a special scratched finish

MATERIALS

Anodised aluminium
Bright aluminium
Colour - coated aluminium
Stainless steel - AISI 304 - DIN 1.4301
Stainless steel - AISI 316 – DIN 1.4401
Polished brass
Chromium - plated brass
Co-extruded PVC - Rigid/Plasticized

For further information, please refer to the section “MATERIALS AND CHARACTERISTICS” at the end of the current Price List Catalogue.

INSTALLATION

Installation with adhesive
Use appropriate personal protective equipment (PPE), such as cut-resistant gloves, when handling the profile.
Remove the profile from its packaging.
Check that the thickness of the wall or floor covering to be installed does not exceed the height of the selected profile.
Where present, remove the protective and/or heat-shrink film used to protect the product finish.
Measure the length of the perimeter to be protected and pre-cut the profiles to size.
Apply the selected adhesive to the installation surface using a notched trowel and place the profile, aligning it flush with the already installed covering.
Install the remaining covering, ensuring it is flush with the profile and spaced at the appropriate distance to maintain the grout joint (usually between 1 and 2 millimetres).
Fill the joint between the covering and the profile with a suitable sealant.
Carefully clean the grout or any other installation residues using a soft sponge and water within 10 minutes of application.

CARE AND MAINTENANCE

The care and maintenance of the materials used for the manufacture of these profiles are closely related to the type of alloy and/or finish employed.
The following guidelines describe the operations required to restore the profile, as much as possible, to its original appearance.
These instructions are intended to provide general guidance on the timing and methods for cleaning; however, they must be assessed on a case-by-case basis.
It should be noted that specific responsibilities apply at every stage of the product's life cycle, starting from installation.

Aluminium
Aluminium does not require specific maintenance and can be easily cleaned using colourless alcohol diluted with water or neutral detergents diluted with water (e.g. products from the MAPEI ULTRACARE range). Do not use acidic or alkaline detergents.
Rinsing must be carried out using water only, with non-abrasive sponges and/or cloths to avoid scratching and/or damaging the finish.
No maintenance with polishing products or similar substances is required.
Cement, adhesive and grouting materials must be promptly and carefully removed from the visible surface of the profile.

Stainless steel
Stainless steel does not require specific maintenance and can be easily cleaned using hot water and soap or neutral detergents diluted with water (e.g. products from the MAPEI ULTRACARE range). Do not use acidic detergents.
Rinsing must be carried out using water only, with non-abrasive sponges and/or cloths to avoid scratching and/or damaging the finish.
In the case of surfaces exposed to atmospheric or aggressive agents, periodic cleaning of the stainless steel profile is recommended in order to preserve the surface appearance and prevent the onset of corrosion.
For profiles with a brushed finish, always clean in the direction of the brushing and never across it.
Avoid leaving objects or tools made of common steel (such as brushes or steel wool) in prolonged contact with stainless steel profiles, as contamination with ferrous particles may cause rust stains on the surface.
Avoid leaving damp cloths or sponges in prolonged contact with stainless steel to prevent the formation of unsightly stains.
In the event of scratches, use a specific cleaner/polish for stainless steel, applying it with a soft cloth.
For maintenance, use commonly available polishing products.


Brass
Brass does not require specific maintenance and can be easily cleaned using colourless alcohol diluted with water or neutral detergents diluted with water (e.g. products from the MAPEI ULTRACARE range). Do not use acidic detergents.
Rinsing must be carried out using water only, with non-abrasive sponges and/or cloths to avoid scratching and/or damaging the finish.
For maintenance, use commonly available polishing products.


PVC
PVC does not require specific maintenance and can be easily cleaned using alcohol diluted in water or neutral detergents diluted in water (e.g. products from the MAPEI ULTRACARE range).
Rinsing must be carried out using water only, with non-abrasive sponges and/or cloths to avoid scratching and/or damaging the finish.
For maintenance, use commonly available polishing products.

FIRE PREVENTION MEASURES

In the event of fire, use chemical fire extinguishers, dry sand or solid extinguishing agents.

PROFILES AND WALL COVERINGS







ZQAN/10 black anodised aluminium

PROANGLE Q

length = 270 cm - pack 20 pcs			H						
ART.	**finishing**		**4,5**	**6**	**8**	**9**	**10**	**11**	**12,5**
ALUMINIUM									
ZQAN/	silver anodised		88772	88875	88876	88877	88878	88879	88880
	titanium anodised		88902	88903	88904	88905	88906	88907	88908
ZQAN/	black anodised		-	-	89205	-	89206	89207	89208
ZQBN/	bright polished silver		88816	88919	88920	88921	88922	88923	88924
ZQBN/	bright polished gold		88933	-	88935	-	88937	-	88939
	bright polished titanium		88956	88964	88966	88968	88970	88972	88974
ZQBRN/	bright polished copper		-	-	-	-	88969	-	88971
ZQBSN/	bright brushed silver		88981	88982	88983	-	88985	88986	88987
	bright brushed gold		88997	-	88999	-	89001	-	89003
ZQTMN/	bright brushed titanium		89013	89014	89015	-	89017	-	89019
ZQBRSN/	bright brushed copper		-	-	89031	-	89033	-	89035
ZQBSN/	bright brushed black		-	-	-	-	89209	89210	89211
ZQAGN/	bright scratched silver		89061	-	89063	-	89065	-	89067
COLOUR-COATED ALUMINIUM									
ZQVN/	colour-coated matt white RAL 9003		-	-	89200	-	89202	89203	89204
	colour-coated white RAL 9003		89077	89076	89079	-	89081	89078	89083
ANTIBACTERIAL COLOUR-COATED ALUMINIUM									
ZQVNH/	colour-coated white RAL 9003		-	-	89080	-	89082	-	89084




ZQAN/ /EI
silver anodised
aluminium

PROANGLE Q - OUTSIDE / INSIDE CORNERS / END CAPS

pack 5 pcs			H						
ART.	**finishing**		**4,5**	**6**	**8**	**9**	**10**	**11**	**12,5**
ALUMINIUM									
ZQAN/ /EI	silver anodised		88809	88882	88883	88884	88885	88886	88887
	titanium anodised		88910	88911	88912	88913	88914	88915	88916
ZQAN/ /EI	black anodised		-	-	89223	-	89224	89225	89226
ZQBN/ /EI	bright polished silver		88829	88926	88927	88928	88929	88930	88931
	bright polished gold		88941	-	88943	-	88945	-	88947
ZQVN/ /EI	colour-coated matt white RAL 9003		-	-	89192	-	89194	89195	89196
	colour-coated white RAL 9003		89085	89086	89087	-	89089	89088	89091
ZQBN/ /EI	bright polished titanium		88976	88978	88980	88984	88988	88992	88996
ZQBRN/ /EI	bright polished copper		-	-	-	-	88977	-	88979
ZQBSN/ /EI	bright brushed silver		88989	88990	88991	-	88993	88994	88995
	bright brushed gold		89005	-	89007	-	89009	-	89011
ZQTMN/ /EI	bright brushed titanium		89021	89022	89023	-	89025	-	89027
ZQBRSN/ /EI	bright brushed copper		-	-	89039	-	89041	-	89043
ZQBSN/ /EI	bright brushed black		-	-	-	-	89227	89228	89229
ZQAGN/ /EI	bright scratched silver		89069	-	89071	-	89073	-	89075

no partial packaging



ZQVN/



ZQVN/10 concrete white colour-coated aluminium

PROANGLE Q - TREND COLOR

TREND COLOR

length = 270 cm - pack 20 pcs			H			
ART.	finishing		8	10	11	12,5
COLOUR-COATED ALUMINIUM						
	TREND COLOR STONE					
	dark brown		89360	89310	89311	89312
	anthracite grey		89093	89095	89106	89097
	ancient grey		89362	89220	89221	89222
	grey		89363	89290	89291	89292
	rust		89094	89096	89107	89098
	bronze		89365	89300	89301	89302
	stone		89366	89280	89281	89282
	greige		89367	89270	89271	89272
	sand		89368	89260	89261	89262
	beige		89369	89250	89251	89252
ZQVN/	white stone		89370	89320	89321	89322
	black stone		89371	89330	89331	89332
	TREND COLOR CONCRETE					
	concrete white		-	89131	89161	89181
	concrete graphite		-	89132	89162	89182
	concrete smoke		-	89133	89163	89183
	concrete mud		-	89134	89164	89184
	concrete sand		-	89135	89165	89185
	solid white		-	89138	89168	89188
	TREND COLOR METAL					
	metal dark		-	89136	89166	89186
	metal light		-	89137	89167	89187

individually packed - Other heights with TREND COLOR finishes are available upon request, with a minimum of 270 meters.



ZQVN/ /EI
sand colour-coated aluminium

PROANGLE Q - TREND COLOR - OUTSIDE / INSIDE CORNERS / END CAPS

pack 5 pcs			H			
ART.	**finishing**		**8**	**10**	**11**	**12,5**
COLOUR-COATED ALUMINIUM						
	TREND COLOR STONE					
	dark brown		89380	89303	89304	89305
	anthracite grey		89100	89102	89108	89104
	ancient grey		89382	89213	89214	89215
	grey		89383	89283	89284	89285
	rust		89101	89103	89109	89105
	bronze		89385	89293	89294	89295
	stone		89386	89273	89274	89275
	greige		89387	89263	89264	89265
	sand		89388	89253	89254	89255
	beige		89389	89243	89244	89245
ZQVN/ /EI	white stone		89390	89340	89341	89342
	black stone		89391	89350	89351	89352
	TREND COLOR CONCRETE					
	concrete white		-	89392	89402	89410
	concrete graphite		-	89394	89403	89411
	concrete smoke		-	89395	89404	89412
	concrete mud		-	89396	89405	89413
	concrete sand		-	89397	89406	89414
	solid white		-	89400	89409	89417
	TREND COLOR METAL					
	metal dark		-	89398	89407	89415
	metal light		-	89399	89408	89416

no partial packaging



ZQAND/

PROANGLE Q - X DESIGN

length = 270 cm - pack 20 pcs			H		
ART.	**finishing**		**8**	**10**	**12,5**
ANODISED ALUMINIUM					
ZQAND/	platinum		31110	31112	31114
	titanium		31120	31122	31124
	brown		31130	31132	31134
	dark brown		31140	31142	31144
	carbon		31150	31152	31154

individually packed

PROANGLE Q - X DESIGN - OUTSIDE / INSIDE CORNERS / END CAPS

pack 5 pcs			H		
ART.	**finishing**		**8**	**10**	**12,5**
ANODISED ALUMINIUM					
ZQAND/EI	platinum		31160	31162	31164
	titanium		31170	31172	31174
	brown		31180	31182	31184
	dark brown		31190	31192	31194
	carbon		31200	31202	31204

no partial packaging



ZQAND/ /EI
brown
anodised
aluminium



PROANGLE Q

length = 270 cm - pack 20 pcs		H						
ART.	**finishing**	**6**	**8**	**9**	**10**	**11**	**12,5**	**15**
STAINLESS STEEL								
ZQIN/	stainless steel AISI 304 - DIN 1.4301	90049	90050	90051	90052	90053	90054	90055
ZQINS/	brushed stainless steel AISI 304 - DIN 1.4301	90100	90101	90102	90103	90104	90105	90106
ZQINP/	sandblasted stainless steel AISI 304 - DIN 1.4301	90130	90131	90132	90133	90134	90135	90136
ZQINX/	stainless steel AISI 316 - DIN 1.4401	-	90107	-	90109	-	90111	-

individually packed - ZQIN/15, ZQINS/15 and ZQINP/15 packaging of 10 pcs


PROANGLE Q - OUTSIDE / INSIDE CORNERS / END CAPS


pack 5 pcs		H						
ART.	**finishing**	**6**	**8**	**9**	**10**	**11**	**12,5**	**15**
STAINLESS STEEL								
ZQIN/ /EI	stainless steel AISI 304 - DIN 1.4301	90064	90065	90066	90067	90068	90069	90070
ZQINS/ /EI	brushed stainless steel AISI 304 - DIN 1.4301	90112	90113	90114	90115	90116	90117	90118
ZQINP/ /EI	sandblasted stainless steel AISI 304 - DIN 1.4301	90137	90138	90139	90140	90141	90142	90143
ZQINX/ /EI	stainless steel AISI 316 - DIN 1.4401	-	90119	-	90121	-	90123	-
METAL								
ZQIM/ /EI	polished steel effect	-	90092	90093	90094	90095	90096	-
ZQIMS/ /EI	brushed steel effect	-	90152	90153	90154	90155	90156	-
ZQIMP/ /EI	sandblasted steel effect	-	90162	90163	90164	90165	90166	-

no partial packaging for ZQIM/ /EI, ZQIMS/ /EI and ZQIMP/ /EI



ZQIN/ /EI
stainless steel
AISI 304 - DIN 1.4301







ZQKN/ /EI
chromium-plated
brass

PROANGLE Q

length = 270 cm - pack 20 pcs			H				
ART.	**finishing**		**4,5**	**8**	**10**	**11**	**12,5**
POLISHED BRASS							
ZQLN/	polished		90022	90056	90057	90063	90058
CHROMIUM-PLATED BRASS							
ZQKN/	chromium plated		88870	90059	90060	90074	90061

individually packed - ZQKN/12,5 packaging of 10 pcs

PROANGLE Q - OUTSIDE / INSIDE CORNERS / END CAPS

length = 270 cm - pack 5 pcs			H				
ART.	**finishing**		**4,5**	**8**	**10**	**11**	**12,5**
BRASS							
ZQLN/ /EI	polished		90062	90071	90072	90075	90073
ZQKN/ /EI	chromium plated		88872	90077	90083	90085	90087



ZQP/



ZQP/8 beige bahama PVC

PROANGLE Q

length = 270 cm			H			
ART.	**finishing**		**6**	**8**	**10**	**12,5**
CO-EXTRUDED PVC						
ZQP/	white		80800	80801	80802	80803
	cream white RAL 9001		80804	80805	80806	80807
	ivory RAL 1015		80808	80809	80810	80811
	beige grey RAL 1019		80812	80813	80814	80815
	stone grey RAL 7030		80816	80817	80818	80819
	light grey RAL 7035		80820	80821	80822	80823
	anthracite		80824	80825	80826	80827
	beige bahama		80832	80833	80834	80835
	brown		80836	80837	80838	80839
pack 20 pcs						
pack 80 pcs						
pack 100 pcs						

no partial packaging

to order the pack of 80 and 100 pcs, mark /80 or /100 after the article code (for example, code 80800 becomes 80800/100)

ZQP/ /EI
white ABS

PROANGLE Q - OUTSIDE / INSIDE CORNERS / END CAPS

pack 12 pcs			H			
ART.	**finishing**		**6**	**8**	**10**	**12,5**
ABS						
ZQP/ / EI	white		80850	80851	80852	80853
	cream white RAL 9001		80854	80855	80856	80857
	ivory RAL 1015		80858	80859	80860	80861
	beige grey RAL 1019		80862	80863	80864	80865
	stone grey RAL 7030		80866	80867	80868	80869
	light grey RAL 7035		80870	80871	80872	80873
	anthracite		80874	80875	80876	80877
	beige bahama		80882	80883	80884	80885
	brown		80886	80887	80888	80889

no partial packaging

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website profilpas.com

PRODUCT FOR PROFESSIONAL USE

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the PROFILPAS product installation.

The most up-to-date TDS can be downloaded from our website profilpas.com

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF PROFILPAS.

PRESCRIPTION

Supply and installation of a (...) profile (type CERFIX PROANGLE Q by Profilpas S.p.A.) with a square section, designed to act as an edge protection profile serving both as a finishing and protective solution for the external corners of ceramic tile coverings, avoiding the unattractive and fragile 45° bevel cut of tile edges.
The profile shall have a height of (...) mm and a length of 270 cm. Thanks to its dimensions, the profile may be installed without joints in a single continuous length, embedding the perforated lateral anchoring flange into the suitable adhesive selected for the installation of the ceramic flooring (e.g. products by Mapei S.p.A.).
During installation, the joint formed between the tile and the profile must be filled with a suitable sealant (e.g. products by Mapei S.p.A.).
Any residues of adhesive, grout or sealant present on the profile must be removed immediately using non-abrasive tools.
Upon completion of installation, any residual cementitious or epoxy materials may be removed using a suitable cleaning product (e.g. products from the MAPEI ULTRACARE range).

Profilpas S.p.A.

Via Albert Einstein, 38, 35010 Cadoneghe (Padova)

+39 049 8878411 www.profilpas.com info@profilpas.com

13207-06-2026-en

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution.