PROFILPAS S.P.A.
VIA EINSTEIN, 38 35010 CADONEGHE (PADOVA)
ITALY
TEL. +39 049 8878411 +39 049 8878412
FAX. +39 049 706692
EMAIL: INFO@PROFILPAS.COM

Movement joints

Cerfix® Projoint DIL

PFFE



Description

PROJOINT DIL PFFE is a load-bearing structural joint composed of two opposing profiles in natural aluminium and an expanding part (+/- 7 mm) in interchangeable plasticized PVC available in black or grey.
The two L-shaped structures are provided with drilled bases (diam. 10 mm) to allow the mechanical fixing with screws included in the supply.
Load capacity for pedestrians, light trolleys, stretchers and cars up to 6,5 kN.
The use of the joint must be verified considering the chemical, mechanical or other stresses of the place where it is installed.
The regulations concerning the joints and the distance between them must be indicated by the project architect or the work supervisor (with reference to the regulations of the country).

Materials

Natural aluminium

Al-Mg-Si aluminium, heat-treated in T6 (6060 T6)
The outer surface must be protected from scratches and rubbing. They present a strong resistance to chemical and atmospheric agents. When wet, concrete and its derivatives produce alkaline substances which can corrode metal (forming aluminium hydroxide) when allowed to react with the surface. For this reason, the visible surface of the profile must be quickly and delicately cleaned to remove any concrete, adhesive or grouting substances and detergents.

Plasticized PVC

Plasticised PVC compound, lead-free, self-extinguishing. Stabilised based on Ca-Zn salts.
Resistant to temperatures between -20°C and +60°C.

General note on metals

Aluminium is not resistant to all chemical compounds. Consequently, contact with particularly aggressive products like hydrochloric acid (HCl) and phosphoric acid (H3P04) should be avoided.
Products generally used to clean stone, ceramic and porcelain tiles, such as muriatic acid, ammonia and bleach, damage the surface finish on the metal and can cause intense corrosion. Moreover, any residues of concrete, adhesive, and grouting materials must always be removed from the surface of the profiles as quickly and delicately as possible.
If adhesive tape is used to cover the profile, it must not be left any longer than an hour.

Installation

Remove the profile from the packaging.
Measure the length required and cut the profile to this length using an appropriate tool.
Fix the profile to the tiles by using mechanical dowels (included in the supply).
Remove any excess grout, adhesive, solvents etc. with a soft sponge and water within ten minutes of application.

PROFILPAS S.P.A.
VIA EINSTEIN, 38 35010 CADONEGHE (PADOVA)
ITALY
TEL. +39 049 8878411 +39 049 8878412
FAX. +39 049 706692
EMAIL: INFO@PROFILPAS.COM

Care and maintenance

Care and maintenance procedures for the materials used to make these profiles depends largely on the type of alloy and/or finish used.
The instructions provided below describe the operations to be performed on the profile to restore it as much as possible to its original condition.
The purpose of this document is to provide as many general indications as possible to guide you on when and how to clean the product, but they should also be verified on a case-by-case basis.
It should be pointed out there are specific responsibilities in each part of the product's life cycle, starting from when it is installed the first time.

Aluminium

No special maintenance is required and aluminium products can be easily treated with colourless alcohol in a water solution or using ordinary detergents, provided they do not contain acid (hydrochloric or hydrofluoric).
Detergent products made by multiple manufacturers and sold under a variety of commercial brands can generally be used for cleaning.

Generally speaking, there are three types of products:

- Alkaline
- Neutral
- Acid

For cleaning purposes, we recommend using a neutral detergent diluted in water then rinsing with water only, using a non-abrasive sponge and/or cloth to avoid scratching and/or damaging the anodized surface.

During cleaning, the following aspects must be kept in mind at all times:

- Do not use acid or alkaline detergents because they could damage the aluminium;
- Do not use products and/or abrasive materials;
- Do not use organic solvents on painted surfaces;
- Do not use detergents without first checking their chemical composition;
- Do not apply detergents straight onto the surface to be cleaned;
- Surfaces must be “cold” (max T°= 30°C) during cleaning and not exposed to direct sunlight;
- Detergents used in cleaning must also be “cold” (max T° = 30°C) and steam sprays should not be used.

In any case, the final stage in the cleaning process is always sufficient rinsing of the parts treated with water. They must then be immediately dried using soft fabric or leather cloths. Polishes or similar products are not required.

Clean profiles carefully as soon as required, following the instructions on the product package, to prevent any residues of concrete, grout or similar substances from attacking the surface.

PVC

Does not need any special maintenance; they can be easily treated with colourless alcohol diluted in water or using normal detergents, provided they are not acid or alkaline based and also diluted in water; use only water for the final rinse.
Use non-abrasive sponges or cloths which will not scrape the surface.

Fire prevention measures


In the event of fire, use chemical fire extinguishers, dry sand or solid extinguishing agents.


Notes


These profiles must be handled with caution, being careful to wear suitable gloves to prevent injury and/or cuts to the hands.
The instructions and specifications provided here are the product of our experience but are only a guide, should not be considered exhaustive and must be confirmed by extensive practical applications.
Profilpas declines any responsibility for damage to people or things resulting from improper use of the product.
Users must establish for themselves if the product is suitable for the required used and they bear full responsibility for any incorrect installation of the material.

PROFILPAS S.P.A.
VIA EINSTEIN, 38 35010 CADONEGHE (PADOVA)
ITALY
TEL. +39 049 8878411 +39 049 8878412
FAX. +39 049 706692
EMAIL: INFO@PROFILPAS.COM

PROJOINT DIL PFFE








PROFILPAS S.P.A.
VIA EINSTEIN, 38 35010 CADONEGHE (PADOVA)
ITALY
TEL. +39 049 8878411 +39 049 8878412
FAX. +39 049 706692
EMAIL: INFO@PROFILPAS.COM

PROJOINT DIL PBE



PFFE/20




smooth rubber striated rubber

PROJOINT DIL

length = 300 cm - pack 5 pcs		H
ART.	**finishing**	
ALUMINIUM		
	natural aluminium + smooth grey rubber	99596
	natural aluminium + smooth black rubber	99597
PFFE/20/		
	natural aluminium + striated grey rubber	99598
	natural aluminium + striated black rubber	99599

no partial packaging - profiles are provided with accessories for mechanical fixing



PFFE/30




smooth rubber striated rubber

PROJOINT DIL

length = 300 cm - pack 5 pcs		H
ART.	**finishing**	
ALUMINIUM		
	natural aluminium + smooth grey rubber	99600
	natural aluminium + smooth black rubber	99601
PFFE/30/		
	natural aluminium + striated grey rubber	99602
	natural aluminium + striated black rubber	99603

no partial packaging - profiles are provided with accessories for mechanical fixing



PFFE/40



smooth rubber striated rubber

PROJOINT DIL

length = 300 cm - pack 5 pcs		H
ART.	**finishing**	
ALUMINIUM		
	natural aluminium + smooth grey rubber	99604
	natural aluminium + smooth black rubber	99605
PFFE/40/		
	natural aluminium + striated grey rubber	99606
	natural aluminium + striated black rubber	99607

no partial packaging - profiles are provided with accessories for mechanical fixing

We suggest the use of the black insert.