
CERFIX PRONIVEL M

Profiles for floors of different height



DESCRIPTION

Cerfix Pronivel M is a stainless steel transition profile having a sloped section designed to connect floor covering of different thicknesses.
The profile is available for ceramic tiles with a total thickness (including adhesive) of 8 mm and 10 mm, which can be used to connect to flooring that is 4 mm thick, such as carpet or LVT.
Cerfix Pronivel M can also be used as a finishing and protective profile for 135° external corners in ceramic tile installations.



MIN/10

MATERIALS

Stainless steel - AISI 304 - DIN 1.4301

For further information, please refer to the section “MATERIALS AND CHARACTERISTICS” at the end of the current Price List Catalogue.

INSTALLATION

Installation with adhesive
Use appropriate personal protective equipment (PPE), such as cut-resistant gloves, when handling the profile.
Remove the profile from its packaging.
Check that the thickness of the wall or floor covering to be installed does not exceed the height of the selected profile.
Where present, remove the protective and/or heat-shrink film used to protect the product finish.
Measure the length of the perimeter to be protected and pre-cut the profiles to size.
Apply the selected adhesive to the installation surface using a notched trowel and place the profile, aligning it flush with the already installed covering.
Install the remaining covering, ensuring it is flush with the profile and spaced at the appropriate distance to maintain the grout joint (usually between 1 and 2 millimetres).
Fill the joint between the covering and the profile with a suitable sealant.
Carefully clean the grout or any other installation residues using a soft sponge and water within 10 minutes of application.

CARE AND MAINTENANCE


The care and maintenance of the materials used for the manufacture of these profiles are closely related to the type of alloy and/or finish employed.
The following guidelines describe the operations required to restore the profile, as much as possible, to its original appearance.
These instructions are intended to provide general guidance on the timing and methods for cleaning; however, they must be assessed on a case-by-case basis.
It should be noted that specific responsibilities apply at every stage of the product's life cycle, starting from installation.

Stainless steel
Stainless steel does not require specific maintenance and can be easily cleaned using hot water and soap or neutral detergents diluted with water (e.g. products from the MAPEI ULTRACARE range). Do not use acidic detergents.
Rinsing must be carried out using water only, with non-abrasive sponges and/or cloths to avoid scratching and/or damaging the finish.
In the case of surfaces exposed to atmospheric or aggressive agents, periodic cleaning of the stainless steel profile is recommended in order to preserve the surface appearance and prevent the onset of corrosion.
For profiles with a brushed finish, always clean in the direction of the brushing and never across it.
Avoid leaving objects or tools made of common steel (such as brushes or steel wool) in prolonged contact with stainless steel profiles, as contamination with ferrous particles may cause rust stains on the surface.
Avoid leaving damp cloths or sponges in prolonged contact with stainless steel to prevent the formation of unsightly stains.
In the event of scratches, use a specific cleaner/polish for stainless steel, applying it with a soft cloth.
For maintenance, use commonly available polishing products.


FIRE PREVENTION MEASURES

In the event of fire, use chemical fire extinguishers, dry sand or solid extinguishing agents.

PROFILES FOR FLOORS OF DIFFERENT HEIGHT



MIN/10



MIN/10
application
for floors of
different height

Complete the article code with H measure
(for example MIN/ for H=10 becomes MIN/10)

PRONIVEL M

length = 270 cm - pack 10 pcs			H	
ART.	**finishing**		**8**	**10**
MIN/	polished stainless steel AISI 304 - DIN 1.4301		93023	93024

individually packed

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website profilpas.com

PRODUCT FOR PROFESSIONAL USE

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the PROFILPAS product installation.

The most up-to-date TDS can be downloaded from our website profilpas.com

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF PROFILPAS.

PRESCRIPTION

Supply and installation of a (...) profile (type CERFIX PRONIVEL M by Profilpas S.p.A.) having a sloped section, designed to provide a transition between floors at different levels as well as an edge protection profile serving both as a finishing and protective solution for the 135° external corners of ceramic tile coverings.
The profile shall have a height of (...) mm and a length of 270 cm. Thanks to its dimensions, the profile may be installed without joints in a single continuous length, embedding the perforated lateral anchoring flange into the suitable adhesive selected for the installation of the ceramic flooring (e.g. products by Mapei S.p.A.).
During installation, the joint formed between the tile and the profile must be filled with a suitable sealant (e.g. products by Mapei S.p.A.).
Any residues of adhesive, grout or sealant present on the profile must be removed immediately using non-abrasive tools.
Upon completion of installation, any residual cementitious or epoxy materials may be removed using a suitable cleaning product (e.g. products from the MAPEI ULTRACARE range).

Profilpas S.p.A.

Via Albert Einstein, 38, 35010 Cadoneghe (Padova)

+39 049 8878411 www.profilpas.com info@profilpas.com

13212-06-2026-en

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution.