
CERFIX PROTEC CPVV

Supports for outdoor raised floors - Accessories for installation
Profiles for balconies and terraces



DESCRIPTION

Cerfix Protec CPVV is a range of colour-coated aluminium perimeter profiles designed for the vertical closure of outdoor raised flooring systems.
Cerfix Protec CPVV can also be used to protect and finish the outer edges of terraces and balconies where 20 mm-thick tiles are glued.
The profiles are available in three colours (ash grey RAL 7038, ancient grey and stone) and in total heights of 100, 120 and 150 mm.
The product range is completed by special components such as outside/inside corners and junctions.



CPVV/

FEATURES AND BENEFITS

- The ideal solution for the vertical perimeter closure of outdoor raised floors
- Available in total heights of 100, 120 and 150 mm
- Can be installed with 20 mm thick glued tiles

MATERIALS

Colour-coated aluminium

For further information, please refer to the section “MATERIALS AND CHARACTERISTICS” at the end of the current Price List Catalogue.

INSTALLATION

Installation for outdoor raised floor

Use appropriate PPE, such as cut-resistant gloves, when handling the profile.
Remove the profile from the packaging.
Measure the length of the perimeter to be protected and pre-cut the profiles to size, allowing for an expansion gap of approximately 5 mm between the individual elements.
Apply the pre-cut profiles on the perimeter supports of the outdoor raised floor, ensuring the previously indicated gap of approximately 5 mm between the elements.
Install the corners between the individual elements that are perpendicular to each other.
Install the junctions between the individual elements that are next to each other, gluing them to only one of the profiles to allow for expansion.

Installation with adhesive

Use appropriate PPE, such as cut-resistant gloves, when handling the profile.
Clean and prepare the installation surface by removing dust or any loose material.
Remove the profile from their packaging.
Measure the length of the perimeter to be protected and pre-cut the profiles to size, allowing for an expansion gap of approximately 5 mm between the individual elements.
Apply the pre-cut profiles along the perimeter of the balcony using the selected adhesive taking care to insert the corners and the junctions in advance, ensuring the previously indicated gap of approximately 5 mm between the elements and a gap of approximately 10 mm from the balcony front edge.
Glue the junctions – which have already been inserted - to only one of the two profiles, so as to allow the profiles to expand. Then seal the inner side of the junctions with MAPESIL AC*.
Maintain a gap of approximately 3 mm between the tiles and the edge of the profiles, which must subsequently be filled with MAPESIL AC*.

*For product installation, please refer to the relevant technical data sheet.

CARE AND MAINTENANCE


The care and maintenance of the materials used for the manufacture of these profiles are closely related to the type of alloy and/or finish employed.
The following guidelines describe the operations required to restore the profile, as much as possible, to its original appearance.
These instructions are intended to provide general guidance on the timing and methods for cleaning; however, they must be assessed on a case-by-case basis.
It should be noted that specific responsibilities apply at every stage of the product's life cycle, starting from installation.

Aluminium
Aluminium does not require specific maintenance and can be easily cleaned using colourless alcohol diluted with water or neutral detergents diluted with water (e.g. products from the MAPEI ULTRACARE range). Do not use acidic or alkaline detergents.
Rinse using clean water only, employing non-abrasive sponges and/or cloths to avoid scratching or damaging the finish.
No maintenance with polishing products or similar substances is required.
Cement, adhesive and grouting materials must be promptly and carefully removed from the visible surface of the profile.

FIRE PREVENTION MEASURES

In the event of fire, use chemical fire extinguishers, dry sand or solid extinguishing agents.


SUPPORTS FOR OUTDOOR RAISED FLOORS - ACCESSORIES FOR INSTALLATION - PROFILES FOR BALCONIES AND TERRACES



CPVV/

PROTEC


length = 270 cm - pack 5 pcs			H		
ART.	**finishing**		**100**	**120**	**150**
COLOUR-COATED ALUMINIUM					
CPVV/	ash grey RAL 7038		87130	87133	87136
	ancient grey		87131	87134	87137
	stone		87132	87135	87138



CPVV/ /EI

90° OUTSIDE CORNER

pack 5 pcs			H		
ART.	**finishing**		**100**	**120**	**150**
COLOUR-COATED ALUMINIUM					
CPVV/ /EI	ash grey RAL 7038		87187	87190	87193
	ancient grey		87188	87191	87194
	stone		87189	87192	87195



CPVV/ /G

JUNCTION

width = 100 cm - pack 5 pcs			H		
ART.	**finishing**		**100**	**120**	**150**
COLOUR-COATED ALUMINIUM					
CPVV/ /G	ash grey RAL 7038		87217	87220	87223
	ancient grey		87218	87221	87224
	stone		87219	87222	87225

no partial packaging

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website profilpas.com

PRODUCT FOR PROFESSIONAL USE

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the PROFILPAS product installation.

The most up-to-date TDS can be downloaded from our website profilpas.com

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF PROFILPAS.

PRESCRIPTION (PROFILES FOR BALCONIES AND TERRACES)

Supply and installation of a colour-coated aluminium profile (type CERFIX PROTEC by Profilpas S.p.A.), designed to protect and finish the external edges of terraces and balconies.
The profile, engineered with a linear cross-section of various heights, shall have a tile bonding height of 20 mm and a length of 270 cm. Thanks to its dimensions, the profile may be installed without joints in a single continuous length, embedding the perforated lateral anchoring flange into the suitable adhesive selected for the installation of the ceramic flooring (e.g. products by Mapei S.p.A.). The profile shall also be supplied complete with matching metal accessories.
During installation, the joint formed between the tile and the profile must be filled with a suitable sealant (e.g. products by Mapei S.p.A.). Any residues of adhesive, grout or sealant present on the profile must be removed immediately using non-abrasive tools. Upon completion of installation, any residual cementitious or epoxy materials may be removed using a suitable cleaning product (e.g. products from the MAPEI ULTRACARE range).

Profilpas S.p.A.

Via Albert Einstein, 38, 35010 Cadoneghe (Padova)

+39 049 8878411 www.profilpas.com info@profilpas.com

13433-08-2026-en

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution.