CERFIX PROTRIM N

External corners profiles



DESCRIPTION

Cerfix Protrim N is a range of profiles particularly suitable for finishing and protecting the external corners of ceramic tile coverings. Its rounded shape harmoniously defines the edge, avoiding the unattractive and fragile 45° tile mitre cut.
The profiles are also particularly suitable for finishing and protecting stair edges in a wide variety of materials such as ceramic, stone, or other materials. They can also be used as finishing profiles for worktops and platforms.
Cerfix Protrim N is particularly resistant to chemical agents, atmospheric conditions, and mechanical stress. The version made of AISI 316 – DIN 1.4401 stainless steel offers improved corrosion resistance and is therefore recommended for applications in areas subject to higher chemical exposure.
Special accessories are available for the creation of external and internal corners, ensuring uniformity and linear continuity of the finish.



RIN/ RINS/ RINX/

FEATURES AND BENEFITS

- It protects the corners of ceramic coverings
- It prevents awkward 45° corner cutting of tiles
- Available heights from 8 to 12,5 mm

MATERIALS

Stainless steel - AISI 304 - DIN 1.4301
Stainless steel - AISI 316 – DIN 1.4401

For further information, please refer to the section “MATERIALS AND CHARACTERISTICS” at the end of the current Price List Catalogue.

INSTALLATION

Installation with adhesive
Use appropriate personal protective equipment (PPE), such as cut-resistant gloves, when handling the profile.
Remove the profile from its packaging.
Check that the thickness of the wall or floor covering to be installed does not exceed the height of the selected profile.
Where present, remove the protective and/or heat-shrink film used to protect the product finish.
Measure the length of the perimeter to be protected and pre-cut the profiles to size.
Apply the selected adhesive to the installation surface using a notched trowel and place the profile, aligning it flush with the already installed covering.
Install the remaining covering, ensuring it is flush with the profile and spaced at the appropriate distance to maintain the grout joint (usually between 1 and 2 millimetres).
Fill the joint between the covering and the profile with a suitable sealant.
Carefully clean the grout or any other installation residues using a soft sponge and water within 10 minutes of application.

CARE AND MAINTENANCE

The care and maintenance of the materials used for the manufacture of these profiles are closely related to the type of alloy and/or finish employed.
The following guidelines describe the operations required to restore the profile, as much as possible, to its original appearance.
These instructions are intended to provide general guidance on the timing and methods for cleaning; however, they must be assessed on a case-by-case basis.
It should be noted that specific responsibilities apply at every stage of the product's life cycle, starting from installation.

Stainless steel
Stainless steel does not require specific maintenance and can be easily cleaned using hot water and soap or neutral detergents diluted with water (e.g. products from the MAPEI ULTRACARE range). Do not use acidic detergents.
Rinsing must be carried out using water only, with non-abrasive sponges and/or cloths to avoid scratching and/or damaging the finish.
In the case of surfaces exposed to atmospheric or aggressive agents, periodic cleaning of the stainless steel profile is recommended in order to preserve the surface appearance and prevent the onset of corrosion.
For profiles with a brushed finish, always clean in the direction of the brushing and never across it.
Avoid leaving objects or tools made of common steel (such as brushes or steel wool) in prolonged contact with stainless steel profiles, as contamination with ferrous particles may cause rust stains on the surface.
Avoid leaving damp cloths or sponges in prolonged contact with stainless steel to prevent the formation of unsightly stains.
In the event of scratches, use a specific cleaner/polish for stainless steel, applying it with a soft cloth.
For maintenance, use commonly available polishing products.

FIRE PREVENTION MEASURES

In the event of fire, use chemical fire extinguishers, dry sand or solid extinguishing agents.

PROFILES FOR EXTERNAL CORNERS



RIN/
RINS/
RINX/

PROTRIM N

length = 270 cm - pack 20 pcs			H		
ART.	**finishing**		**8**	**10**	**12,5**
STAINLESS STEEL					
RIN/	stainless steel AISI 304 - DIN 1.4301		92353	92356	92359
RINS/	brushed stainless steel AISI 304 - DIN 1.4301		92354	92357	92360
RINX/	stainless steel AISI 316 - DIN 1.4401		92355	92358	92361

individually packed



TIEN/ stainless steel AISI 304 - DIN 1.4301

PROTRIM N - OUTSIDE CORNER

pack 5 pcs			H		
ART.	**finishing**		**8**	**10**	**12,5**
TIEN/	stainless steel AISI 304 - DIN 1.4301		92813	92816	92819
TIENS/	brushed stainless steel AISI 304 - DIN 1.4301		92814	92817	92820
TIENX/	stainless steel AISI 316 - DIN 1.4401		92815	92818	92821



TIIN/ stainless steel AISI 304 - DIN 1.4301

PROTRIM N - INSIDE CORNER

pack 5 pcs			H		
ART.	**finishing**		**8**	**10**	**12,5**
TIIN/	stainless steel AISI 304 - DIN 1.4301		92828	92831	92834
TIINS/	brushed stainless steel AISI 304 - DIN 1.4301		92829	92832	92835
TIINX/	stainless steel AISI 316 - DIN 1.4401		92830	92833	92836

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website profilpas.com

PRODUCT FOR PROFESSIONAL USE

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the PROFILPAS product installation.

The most up-to-date TDS can be downloaded from our website profilpas.com

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF PROFILPAS.

PRESCRIPTION

Supply and installation of a (...) profile (type CERFIX PROTRIM N by Profilpas S.p.A.) with a rounded section, designed to act as an edge protection profile serving both as a finishing and protective solution for the external corners of ceramic tile coverings, avoiding the unattractive and fragile 45° bevel cut of tile edges.
The profile shall have a height of (...) mm and a length of 270 cm. Thanks to its dimensions, the profile may be installed without joints in a single continuous length, embedding the perforated lateral anchoring flange into the suitable adhesive selected for the installation of the ceramic flooring (e.g. products by Mapei S.p.A.).
During installation, the joint formed between the tile and the profile must be filled with a suitable sealant (e.g. products by Mapei S.p.A.). Any residues of adhesive, grout or sealant present on the profile must be removed immediately using non-abrasive tools. Upon completion of installation, any residual cementitious or epoxy materials may be removed using a suitable cleaning product (e.g. products from the MAPEI ULTRACARE range).

Profilpas S.p.A.

Via Albert Einstein, 38, 35010 Cadoneghe (Padova)

+39 049 8878411 www.profilpas.com info@profilpas.com

13210-06-2026-en

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution.