PP LEVEL MINI

Supports for outdoor raised floors with reduced heights



DESCRIPTION

PP level MINI is a range of supports for the installation of outdoor raised floors. The range consists of:

- PP level MINI 10/15: Support for self-supporting ceramic, natural stone, or concrete slabs with a 4 mm joint
- PP level MINI 10/15/TD: Support for decking joists
- PP level MINI P/5: 5 mm thickness extension

PP level MINI 10/15 and **PP level MINI 10/15/TD** are **fixed-head supports** adjustable in height from 10 to 15 mm thanks to the integrated adjustment ring; they can be further extended up to 30 mm by adding **PP level MINI P/5** extensions under the base (up to a maximum of three extensions).
PP level MINI is the ideal solution for terraces, pool edges, pedestrian walkways, etc. where it is necessary to install raised floors with limited heights.

FEATURES AND BENEFITS

- Millimeter adjustment from 10 to 15 mm
- Height extendable up to 30 mm thanks to P/5 extensions
- Available with head for self-supporting tile flooring with 4 mm joints or with head for decking joist covering
- Easy and quick to install
- Maximum durability

MATERIALS

PP
Polypropylene, colour black, resistant to both acid and basic solutions and to atmospheric agents.
Operating temperature -40°C + 75°C.
Classification of reaction to fire (EN 13501-1:2018): E
The mechanical characteristics remain unchanged over time.

ENVIRONMENTAL IMPACT AND END-OF-LIFE PRODUCT

Non-hazardous, recyclable waste.
Bases and extensions are made of polypropylene (PP5).
All of the above components are 100% recyclable.

DIMENSIONS

Diameter PP Level MINI	156 mm
Support surface	191 cmq
Spacer fin thickness	4 mm
Fin height	10 mm (10/15), 18 mm (10/15/TD)

TECHNICAL CHARACTERISTICS

Compressive strength	27,15 kN

INSTALLATION


Installation is made by dry positioning of the support on the existing surface: concrete slab, waterproof membrane*, rigid insulating panel**, ceramic floors, stone floors, etc.
The installation surface must be smooth, clean, flat, compact, stable, mechanically resistant and must maintain these characteristics over time.
No adhesives or other types of fixings are required. We recommend interposing a Profilpas rubber mat between the installation surface and the support.
The product requires specialised labour for installation.

*Make sure that the membrane used does not obstruct the water drainage holes.
**Check the mechanical characteristics of the rigid insulating panel with the manufacturer


CONSUMPTION PER SQUARE METRE



30x60
40x40
50x50
60x60



40x80 30x120
45x90 40x120
60x90 60x120



80x80
90x90
100x100
120x120

SUPPORTI AL MQ
SUPPORTS PER SQM

DIM. PIASTRELLE TILE SIZE (cm)	30	40	45	50	60	80	90	100	120
30	11,1				5,6				5,6
40		6,5			4,2	6,3			4,2
45			4,9				4,9		
50				4,0					
60	5,6	4,2			2,8		3,7		2,8
80		6,3				6,3			
90			4,9		3,7		4,9		
100								4	
120	5,6	4,2			2,8				2,8

Le indicazioni presenti in queste tabelle sono indicative e variano in base alle dimensioni ed alla geometria dell'area da calcolare.

The indications in these tables are indicative and vary according to the size and geometry of the area to be calculated.

CARE AND MAINTENANCE

PP
No special maintenance required.

FIRE PREVENTION MEASURES

In case of fire, use chemical extinguishing agents, dry sand or solid extinguishing agents.

SUPPORTS FOR OUTDOOR RAISED FLOORS



10/15



10/15/TD



P/5

PP LEVEL MINI

ART.		Cod.	Pack.
10/15	adjustable support from h. 10 to 15 mm	19351	20 pcs
10/15/TD	adjustable support from h. 10 a 15 mm - head for decking	19349	20 pcs
P/5	extension h. 5 mm for art. 10/15 (maximum 3 extensions = +15 mm)	19350	20 pcs

no partial packaging

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.
Please refer to the current version of the Technical Data Sheet, available from our website profilpas.com
PRODUCT FOR PROFESSIONAL USE

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the PROFILPAS product installation.
The most up-to-date TDS can be downloaded from our website profilpas.com
ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF PROFILPAS.

Profilpas S.p.A.
Via Albert Einstein, 38, 35010 Cadoneghe (Padova)
+39 049 8878411 www.profilpas.com info@profilpas.com

13205-11-2025-en

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution.