PROFILPAS S.P.A.
VIA EINSTEIN, 38 35010 CADONEGHE (PADOVA)
ITALY
TEL. +39 049 8878411 +39 049 8878412
FAX +39 049 706692
EMAIL: INFO@PROFILPAS.COM

Skirting
PVC Line

8605



8606



8615



8616



Description

PVC Line 8605, 8606, 8615 and 8616 are a range of a non-toxic and shockproof coextruded PVC (expanded + rigid) skirting board, foiled with UV resistant Alcrom® Plus decorative film.
They must be laid using suitable adhesives (type PP/96).
The PVC Line 8605 series is available in 58 different colors, both plain color and wood decoration, in order to suit any type of floor decor. PDS technology also allows customization on demand with infinite solutions.
In addition to the decorative function, it meets the technical requirement to hide the perimeter expansion space in floating flooring.
PVC Line 8605, 8616, 8615 and 8616 does not contain formaldehyde (UNI EN 717-2 1996:1996), can be used in humid environments (water absorption <1% UNI EN ISO 62:2008), resists the cold liquid aggression (UNI EN 12720:2009).

Materials

Compound PVC vinyl foam lead-free, self-extinguishing. Stabilized salt-based Ca-Zn.

PROFILPAS S.P.A.
VIA EINSTEIN, 38 35010 CADONEGHE (PADOVA)
ITALY
TEL. +39 049 8878411 +39 049 8878412
FAX +39 049 706692
EMAIL: INFO@PROFILPAS.COM

Laying

Laying instructions using Adhesives

Take the skirting board out of the packaging.
Measure and cut the skirting board to the required length with the proper tools.
Verifying that the laying area is perfectly clean and then place the skirting board, now cut to measure, in the correct position, fixing it to the wall with the appropriate adhesive (type Mapei MS 45 or MS 55).
Keep sufficient pressure for a few minutes on the entire length of the skirting board in order to ensure sufficient adhesion to the laying surface.

Care and maintenance

The instructions below describe the operations in order to maintain as much as possible the original appearance of the product.
The intent is to provide all those general guidelines that can serve in the choice of when and how to clean, but they will have to be checked case by case. It must be underlined that, at every stage of product life starting from its installation, there are already definite responsibilities.

PVC - These need no particular maintenance and are easily cleaned with colorless alcohol diluted in water, or with normal detergents diluted in water (though not acid-based products); rinse thoroughly when finished, with water only.
Use a sponge and/or non-abrasive cloth to prevent scratches and/or damage to the surface.

Fire control measures

In case of fire, extinguish with fire-fighting chemical products, dry sand or solid fire-extinguishing agents.

Note


These profiles must be handled with care, taking the necessary steps to use suitable gloves to prevent wounds, such as cuts to the hand.
All indications and instructions herein contained, that comes from our own experience, has to be understood as purely informative and will have to be confirmed through exhaustive practical experience.
Profilpas will not be held responsible for any personal injury or material damage from improper use of the product.
The user is responsible for establishing whether the product is suitable for the task and likewise must assume all responsibility for incorrect laying of material.

PROFILPAS S.P.A.
VIA EINSTEIN, 38 35010 CADONEGHE (PADOVA)
ITALY
TEL. +39 049 8878411 +39 049 8878412
FAX +39 049 706692
EMAIL: INFO@PROFILPAS.COM

8605 – 8606



8606 white RAL 9003 co-extruded PVC



8605


PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.			
8605		white RAL 9003	29175
		white RAL 9010	29177

no partial packaging



8605 covered with Alcrom® Plus film

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC) COVERED WITH ALCROM® PLUS FILM

ART.		decors	
8605		96 white RAL 9010 embossed	29030
		97 black RAL 9005 embossed	29031
8605		99 satin silver	29035
		100 satin steel	29036

no partial packaging



8605 foam PVC covered with Alcrom® Plus film


PVC LINE

length = 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC) COVERED WITH ALCROM® PLUS FILM

ART.	decors		decors		decors		decors	
8605	02	29000	41	29012	1006	29102	1060	29120
	08	29001	44	29013	1009	29103	1063	29121
	09	29002	47	29033	1012	29104	1066	29122
	10	29003	48	29015	1021	29107	1069	29123
	11	29004	65	29018	1024	29108	1081	29127
	12	29005	76	29020	1030	29110	1084	29128
	20	29006	77	29021	1033	29111	1087	29129
	25	29032	78	29022	1036	29112	1090	29130
	32	29007	80	29023	1042	29114	1105	29135
	34	29008	81	29024	1045	29115	1108	29136
	35	29009	92	29026	1051	29117	1111	29137
	36	29010	95	29029	1054	29118		
	40	29011	1003	29101	1057	29119		

no partial packaging - 8605 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters



8606

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.			
8606		white RAL 9003	29227
		white RAL 9010	29229

no partial packaging - 8606 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters

PROFILPAS S.P.A.
VIA EINSTEIN, 38 35010 CADONEGHE (PADOVA)
ITALY
TEL. +39 049 8878411 +39 049 8878412
FAX +39 049 706692
EMAIL: INFO@PROFILPAS.COM


8615 – 8616



8616 black RAL 9004 co-extruded PVC



8615 silver co-extruded PVC



8615


PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.			
8615	☐	white RAL 9003	29353
	☐	white RAL 9010	29355

no partial packaging



8615 decors with film Alcrom® Plus


PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC) COVERED WITH ALCROM® PLUS FILM

ART.		decors	
8615	☐	96 white RAL 9010 embossed	29357
	■	97 black RAL 9005 embossed	29358

no partial packaging
8615 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters



8616

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.			
8616	☐	white RAL 9003	29495

no partial packaging
8616 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters