RAISED TILE PROTECTOR

Supports for outdoor raised floors
Accessories for installation





CO_2 e FULLY OFFSET PRODUCTRS

Residual Greenhouse Gas emissions measured throughout the life cycle of this product using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset for the year 2026 through the acquisition of carbon credits in support of forestry protection projects. For more details on emission calculations and offsetting projects, visit mapei.com.

DESCRIPTION

Super hydrophobic treatment with high contact angle, solvent-free, which significantly reduces water pooling on outdoor raised floors.
Product with very low VOC (Volatile Organic Compound) emissions, with a view to protecting the health of both applicators and end users, EC1 Plus certified.

FEATURES AND BENEFITS

- Reduces water pooling by over 50%
- High contact angle
- Quick and simple application
- Ready to use
- UV resistant
- Very low VOC emissions

APPLICATION PROCEDURE

Clean the surfaces to be treated using a cleaner from the **UltraCare range by Mapei** (e.g. **UltraCare Multicleaner, UltraCare Acid Cleaner, UltraCare Keranet, UltraCare Rust Remover** or **UltraCare HD Cleaner**, depending on the type of dirt and surface; refer to the specific technical data sheets).

Raised Tile Protector must be applied on a dry surface.

Raised Tile Protector is ready for use. Shake before use. Apply the product with a roller, fleece or flat brush over the entire surface to be treated. Wait approximately 10-15 minutes and then remove any product residue with a clean cloth, taking care not to leave any residue that could cause unsightly marks. During warmer periods, it may be necessary to remove any excess product much more quickly to prevent it from drying on the surface, which could cause marks/stains on the flooring.

The surface is walkable after approximately 8 hours and the product is active 12-24 hours after application.

RECOMMENDATIONS

- Do not apply on surfaces previously treated with waxes or waterproofing agents.
- Always carry out preliminary tests to check compatibility with the surface to be treated and any colour variations.
- The product does not protect surfaces from chemical aggression.
- Depending on the traffic to which the surfaces will be subjected during use, it is advisable to periodically check the water-repellent properties of the treated surfaces, considering any seasonal or annual maintenance of the same, by repeating the application cycle described above.

CONSUMPTION

Indicative coverage: from 10 to 30 m^2 per litre (one coat), depending on surface absorption. Yield is strongly influenced by the degree of absorption and the surface finish of the treated material.

PACKAGING

Raised Tile Protector is available in 1 litre jerrycan.

STORAGE

Raised Tile Protector, stored in its original packaging, has a shelf life of 24 months.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

For safe use of the product, please consult the latest version of the Safety Data Sheet, available on our website www.profilpas.com.

PRODUCT FOR PROFESSIONAL USE

TECHNICAL DATA (typical values)

CHEMICAL-PHYSICAL PROPERTIES	
pH (+20°C) pure product:	7
Specific weight (+20°C):	1,2 g/cm^3
Physical state:	liquid
Colour:	milky
Odour:	characteristic

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application.
Please refer to the current version of the Technical Data Sheet, available from our website www.profilpas.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the PROFILPAS product installation.
The most up-to-date TDS can be downloaded from our website www.profilpas.com .
ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF PROFILPAS.

Profilpas S.p.A.
Via Albert Einstein, 38, 35010 Cadoneghe (Padova)
+39 049 8878411 www.profilpas.com info@profilpas.com

13428-08-2026-en

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution