weberdry prime SB (KSA)

Solvent based bitumen primer

Waterproofing



Leb	Jordan	Egypt	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	-	-	18L 200L	-

PRODUCT

weberdry prime SB is solvent-based primer, used for the preparation of surface to be waterproofed, with the aim of improving adherence of the waterproofing bituminous membranes to the substrate. The product can be applied on the majority of traditional surface in building.

PROPERTIES

- Excellent adherence to all traditional substrate in building
- High penetration capacity on porous surface
- Excellent coverage rate
- Fast- drying
- Strengthens surfaces, eliminating loose dust

CHARACTERISTICS	
Appearance	Black colored liquid
Density at 25°C	0.90±0.05 g/cm³
Saybolt Furol Viscosity 25°C	75-125S
Flash point	Min. 38°C
Water solubility	Insoluble
Benzene solubility	Soluble
Toluens solubility	Soluble
Drying time at 25°C	2 hours

APPLICABLE STANDARDS

ASTM- D 41.

INSTRUCTIONS FOR USE

a) The surface must be dry, free from dust, loose or badly adhered particles and any dirt in general, including any pity or anti-adherent remains.
b) **weberdry prime SB** can be applied on smooth or rough surfaces. However, it is not advisable to apply the product on very polished surfaces, i.e. burnished or glazed, as these would have to be slightly roughened prior to application.
c) Hollows and unevenness must be repaired with cement mortar, to obtain an even surface.

Application of **weberdry prime SB**
weberdry prime SB is supplied ready to use and is cold applied using a brush or roller. It can also be applied with a normal paint spray.
The tools used, including the spray nozzle, must be cleaned with White Spirit type solvent as often as necessary to avoid **weberdry prime SB** from drying on the tools and spoiling them, other than, of course, during any work break, lunch break and at the end ofworking day.

COVERAGE RATE

This depends on the smoothness or roughness and porosity of

the surface.
Coverage rate around 0.2-0.3L/m² per coat.

STORAGE

Maximum One Year in well closed containers and protected against weathering and stored at temperature between 5°C and 30°C.

.

SAFETY PRECAUTIONS

Application should be done in a ventilated area away from any heat source. Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water.
If swallowed, do not induce vomiting, in both cases seek medical attention. In case of fire, use CO2 foam to extinguish. Tightly seal containers when not in use, store them away from heat and carefully dispose empty ones.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding SAL). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

SAINT-GOBAIN