weberfloor 255 SC

Liquid Surface hardener for concrete and mortar



Flooring

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
5lit	5lit	5lit	5lit	5lit	5lit	5lit	5lit
20lit	20lit	20lit	20lit	20lit	20lit	20lit	20lit
25lit	25lit	25lit	25lit	25lit	25lit	25lit	25lit
200lit	200lit	200lit	200lit	200lit	200lit	200lit	200lit

PRODUCT

weberfloor 255 SC is a water based liquid surface hardener and dust proofer. It is based on hard resins that provide a good adhesion to concrete, stones and mortars. It offers high exterior durability and oil, grease and water resistance.

SCOPE OF USE

- Industrial floors
- Parking
- Facade panels
- Terraces
- Stones

CHARACTERISTICS	
Color	Transparent
Density	Around 1.35
pH	10.5

APPLICABLE STANDARDS

ASTM C1315- Type 1.

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrate must be dry, clean, sound and free form greasy matters and dust. Remove all traces of curing compounds, old paints and sealer, and debris which may affect the adhesion. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred. New concrete must be at least 14 days old.

PRODUCT APPLICATION

It is recommended to dilute 1 part of **weberfloor 255 SC** with 1 to 2 parts of clean water in order to facilitate its penetration. **weberfloor 255 SC** is applied using a roller, a brush or an airless spray gun.
Allow the solution to be absorbed into the substrate and remove the surplus.
Two layers are recommended at 24 hours interval.
Allow to dry for few hours before exposure to traffic.

CONSUMPTION

0.150 liters/m²/two coats.

STORAGE

One year after manufacturing date in its original packing non open, protected form frost and heat.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning thoroughly with soap and water. In case of contact

with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain entities. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this datasheet or any information it contains, is prohibited and subject to legal pursuit.

SAINT-GOBAIN